## WALL SCONCE



## Standard Product Specifications

Materials: 20ga. G90 Galvanized Steel and Aluminum Finish: Powder Coated Lens: White Acrylic LED: Integrated LED Array Top/Bottom: Metal Top/Metal Bottom Standard Listing: Wet List to Meet UL 1598 Standard Driver Info: 120V Installation Information: Install by Qualified Electrician Warranty: 2 Years From Date of Shipment

## **DIMENSIONS:**

AUR11 - 11"H x 5"W x 5.75"E AUR16 - 15.375"H x 7.625"W x 9.128"E AUR25 - 25"H x 10.2"W x 15"E AUR26 - 26"H x 9"W x 11.25"E

(Custom Sizes Available; Call Customer Service)





Aurora Wall Sconce



Aurora Post Top

MODEL	FINISH	WATTAGE	KELVIN	OPTIONS
Model AUR11 AUR16 AUR25 AUR26	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color	Wattage   LED12 - 12W LED 1200 Lms   LED21 - 21W LED 2100 Lms   LED23 - 23W LED 2300 Lms   LED36 - 36W LED 3600 Lms	<b>Kelvin</b> <b>30</b> - 30K <b>35</b> - 35K <b>40</b> - 40K <b>50</b> - 50K	Options DV - Dual Volt 120/277V DIM - 0-10V Dimmable EM5 - 500 Lms Emergency* EM12 - 1200 Lms Emergency* *EM on 15"H or Larger
AURPT AURXX *Replace XX with Height Divine Lighting Fabrication & Po		http://www.divinelighting.net		*Back Box Required <b>PMXX</b> - Pendant Mount *Replace XX With Pendant Length in Inches or Feet. PH: 936-494-3900

Divine Lighting Fabrication & Powder Coating, LLC. Conroe, TX http://www.divinelighting.net customerservice@divinelighting.net PH: 936-494-3900 FX: 936-494-3910

As led performance and lumen output becomes more efficient, specifications are subject to change without notice

REV 121522 1000 ACE