

WALL SCONCE CAMBRIDGE



DIMENSIONS:
18"H x 8"W x 4"E
15"H x 8"W x 4"E

| | |
|--------------|--|
| Project: | |
| Location(s): | |
| Type: | |
| Qty: | |
| Date: | |

PRODUCT SPECIFICATIONS

Description:

A Partial Circle Sconce Giving the Feel of an Up/Down Light

Materials:

20ga. G90 Galvanized Steel Pan with 1/4" Square Steel Band Frame

Finish:

Powder Coated

Lens:

White Acrylic

Lens Top / Lens Bottom Standard

LED:

Integrated LED Array

Listing:

Wet List to Meet UL 1598 Standard

Driver Info:

120V

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment



0



1



2



3



4



5



6



7



8



9



11



12



13



14

Perforated



15



16



-EYE

ORDER INFORMATION

Call Factory For Fluorescent Options

| MODEL | PATTERN | FINISH | WATTAGE | KELVIN | LENS | OPTIONS |
|-----------------------------|--------------------------|-----------------------------------------------------------------------------------------------------|---------------------------------------------------------------|--------------------------------------------------------|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Model CAM-188 CAM-158 | Pattern # - Pattern # | Finish DB - Dark Bronze BL - Black WH - White AS - Anodized Silver CC - Custom Color | Wattage LED12 - 12W LED 1200Lms LED21 - 21W LED 2100Lms | Kelvin 30 - 30K 35 - 35K 40 - 40K 50 - 50K | Lens WA - White Acrylic | Options DV - Dual Volt 120/277 MT - Metal Top MB - Metal Bottom LB - Lens Bottom DIM - Dimmable 0-10V EM5 - 500Lm Emergency |

Divine Lighting & Fab., LLC.
3704 Hilltop Dr. Ste. 200

<http://www.divinelighting.net>
customerservice@divinelighting.net

PH: 936-494-3900
FX: 936-494-3910

As led performance and lumen output becomes more efficient, specifications are subject to change without notice

