

Standard Product Specifications


Materials:
Steel
Finish:
Powder Coated
Hand Hole Cover:
Standard on Steel Poles

Pole Height	Pole Bury Depth
8'	2'
10'	
12'	
15'	3'
18'	
20'	4'
24'	
30'	5'

The Chart Above is a Guideline -
Check With an Engineer for Site
Specific Requirements.



**Hand Hole 18" Above
Ground
Access Hole 18" Below
Ground**



Divine Standard Drill Pattern

MODEL	SHAFT	SCHEDULE	LENGTH	BURY DEPTH	OPTIONS	FINISH
Model POLE-DB-RSP (Round Steel Direct Bury)	Shaft 5 - 5"OD	Schedule/Gauge 7 - 7 Gauge	Length(Overall) 8 - 8 Feet 10 - 10 Feet 12 - 12 Feet 15 - 15 Feet 18 - 18 Feet 20 - 20 Feet 30 - 30 Feet	Bury Depth BX' - Custom Bury Depth (In Feet)	Options 190 - (1) 90 Degree Hole 2180 - (2) 180 Degree Holes GFCI - GFCI Receptacle GFCILOCK - GFCI Lock TENON 2 3/8 x 3 TENON 3 x 3 EYE - Eye Hooks	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color

**Customer is responsible for providing fully dimensioned drill patterns when using heads from other manufacturers; otherwise, the standard Divine Lighting drill pattern will be used.

**Customer must specify the orientation of fixtures on the pole when ordering. This information can be found in the options section, e.g. 190, 2180, etc.

**Divine Lighting is not responsible for inconsistencies between poles, fixtures, and parts produced by different manufacturers, and cannot guarantee proper fitting between such components.