

DIMENSIONS:
4.3" W x 3" H x Custom Length

Project:	
Location(s):	
Type:	
Qty:	
Date:	

PRODUCT SPECIFICATIONS

Description:
A Direct/ Indirect Linear Fixture That Offers High Uplight

Materials:
20ga. G90 Galvanized Steel

Finish:
Powder Coated

Lens:
Frosted Acrylic


LED:
Integrated LED Array

Listing:
Dry List to Meet UL 1598 Standard

Driver Info:
120V

Installation Information:
Install by Qualified Electrician

Warranty:
2 Years From Date of Shipment



ORDER INFORMATION
Call Factory For Fluorescent Options

MODEL	FINISH	WATTAGE	KELVIN	LENS	LENGTH	OPTIONS
Model DI/BW43	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color	Wattage (4') LED36 - 36W LED 3600Lm Uplight + 1200Lm Down Light Wattage (8') LEDSD43 - 43W LED 4000Lm Uplight + 1500Lm Down Light LED64 - 64W LED 6400Lm Uplight + 2000Lm Down Light	Kelvin 30 - 30K 35 - 35K 40 - 40K	Lens FA - Frosted Acrylic	Length 4 - 4 Foot Length 8 - 8 Foot Length	Options DV - 120/277 Dual Volt AC50 - 50" Air Craft Cable