


# DIRECT / INDIRECT D/I-LPF & D/I-LPC



**DIMENSIONS:**  
**LPF** - 48"L x 9.625"W x 3.25"H  
**LPC** - 48"L x 7.75"W x 2.5"H

Project:	
Location(s):	
Type:	
Qty:	
Date:	

## PRODUCT SPECIFICATIONS

**Description:**  
 Ambient Lighting For an Office or Task Area. Louvered Center with Optional Perforations

**Materials:**  
 Heavy Gauge Cold-Rolled Steel Housing

**Finish:**  
 Powder Coated

**Lens:**  
 White Opal Acrylic Diffuser

**LED:**  
 Integrated LED Array

**Listing:**  
 Dry List to Meet UL 1598 Standard

**Driver Info:**  
 120V

**Installation Information:**  
 Install by Qualified Electrician

**Warranty:**  
 2 Years From Date of Shipment



LPC  
 Shown with Optional Outer Perforations



LPF  
 Shown with Optional Outer and Top Perforations

\*Also available in LED tube lamps\*

## ORDER INFORMATION

Call Factory For Fluorescent Options

MODEL	FINISH	WATTAGE	KELVIN	MOUNT	OUTER ROW	CENTER ROW	TOP ROW*	LENGTH	OPTIONS
<b>Model</b> D/I-LPF D/I-LPC	<b>Finish</b> DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	<b>Wattage</b> LED64 - 64W LED 6400 Lms LED128 - 128W LED 12800 Lms  <b>Kelvin</b> 30 - 30K 35 - 35K 40 - 40K	<b>Mount</b> AC50 - 50" Aircraft Cable PDXX - Pendant Mount  Replace XX with desired length of pendant rods	<b>Outer Row</b> (Smooth Sides Standard) SPER - Sides Perforated  <b>Center Row</b> LOUV - Louvered LENS - Smooth White Lens	<b>Top Row*(LPF Only)</b> (Smooth Sides Standard) TPER - TPerforated	<b>Length</b> Multiples of 4' 4 - 4 Foot XX - Multiples of 4 Foot	<b>Options</b> DV - 120/277 Dual Volt MOT - Motion Sensor EM - Emergency Backup EM5 - 500 Lm Emergency EM12 - 1200 Lm Emergency DIM0-10V - Dimmable		