

DIRECT / INDIRECT

D/I-SQ48



DIMENSIONS:
48"L x 8"W x 3"H

Project:	
Location(s):	
Type:	
Qty:	
Date:	

PRODUCT SPECIFICATIONS

Description:

Ambient Lighting For an Office or Task Area

Materials:

Extruded Aluminum

Finish:

Powder Coated

Lens:

White Polycarbonate

LED:

Integrated LED Array

Listing:

Dry List to Meet UL 1598 Standard

Driver Info:

120V

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment



ORDER INFORMATION

Call Factory For Fluorescent Options

MODEL	FINISH	WATTAGE	KELVIN	LENGTH	MOUNT	OPTIONS
Model D/I-SQ48	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color	Wattage LED64 - 64W LED 6400 Lms LED128 - 128W LED 12800 Lms <i>*also available in LED tube lamps*</i>	Kelvin 30 - 30K 35 - 35K 40 - 40K	Length 4 - 4 Feet 8 - 8 Feet XX - Length in multiples of 4"	Mount AC50 - 50" Aircraft Cable	Options DV - Dual Volt MOT - Motion EM - Emergency EM5 - 500 Lumen Emergency EM12 - 1200 Lumen Emergency DIM0-10V - 0-10V Dimmable SLT - Slotted Polycarbonate Lens LVR - Louvers