

# AREA LIGHTING

## KH



### DIMENSIONS:

- KH15:** 9.5"W x 3.75"H x 11.75"E
- KH25:** 13.4"W x 3.7"H x 15"E
- KH45:** 15.75"W x 4"H x 22"E
- KH55:** 31.5"W x 4"H x 22"E

Project:	
Location(s):	
Type:	
Qty:	
Date:	

### PRODUCT SPECIFICATIONS

#### Description:

A Contemporary Street Light with Multiple Mounting Options

#### Materials:

Die Cast Aluminum Housing

#### Finish:

Powder Coated

#### Lens:

Tempered Clear Flat Glass

#### LED:

Integrated LED Array

#### Listing:

Wet List to Meet UL 1598 Standard

IP66 Listed

#### Driver Info:


120/277V

#### Installation Information:

Install by Qualified Electrician

#### Warranty:

2 Years From Date of Shipment



**KH15**  
with PMA (Pole Mounting Arm)



**KH25/KH45**  
with KA (Mounting Arm)  
Square Pole



**KH55**



Motion w/ Accessory



**KH25/45 with Hood**



**YOKE (with 2 Piece Swivel)**



**LSF (Large Slip Fitter)**



**WM (Wall Mount)**



**Kard**

### ORDER INFORMATION

Call Factory For Fluorescent Options

MODEL	FINISH	WATTAGE	KELVIN	TYPE	OPTIONS	
<b>Model</b> KH15 KH25 KH45 KH55	<b>Finish</b> DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	<b>Wattage(KH15)</b> LED22 - 22W LED 2700 Lms LED37 - 37W LED 4500 Lms  <b>Wattage(KH25)</b> LED81 - 81W LED 8900 Lms LED112 - 112W LED 14200 Lms	<b>Wattage(KH45)</b> LED167 - 167W LED 20000 Lms LED256 - 256W LED 31000 Lms  <b>Wattage(KH55)</b> (2)LED256 - (2)256W LED 62000 Lms	<b>Kelvin</b> 30 - 30K 40 - 40K 50 - 50K	<b>Type</b> II - Type 2 III - Type 3 IV - Type 4 V - Type 5	<b>Options</b> PC - Photocell H - Housing Hood for KH25/45 KARD - Adaptor for Round Poles MOT - Motion PMA - Pole Mounting Arm WM - Wall Mount KA - Mounting Arm Square Pole LSF - Slip Fitter YOKE - Yoke with 2 Piece Swivel 360S - 360deg Shield (3.75"D)