AREA AND SITE LIGHTING **KH15TS**



Standard Product Specifications

Materials:

Die-Cast Aluminum Housing

Finish:

Powder Coated

Lens:

Tempered Clear Flat Glass

LED:

Integrated LED Array

Listing:

Wet List to Meet UL 1598 Standard

FWC Turtle-Safe 585-595 nm

Driver Info:

120/277V

0-10V Dimmable Standard

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment

DIMENSIONS:

11.75"L x 9.5"W x 7.5"H









KH15TS w/ Wall Mount Bracket



KH15TS w/ Pole Mounting Arm Adapter

MODEL	FINISH	WATTAGE	KELVIN	OPTIONS
Model KH15TS	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color	Wattage LED22 - 22W LED 1159 Lms LED38 - 38W LED 1738 Lms	Kelvin 14 - 14K	Options PC - Photocell MOT - Motion Sensing MA - Square Pole Mounting Arm KHA - Kitty Hawk Arm WM - Wall Mount

Divine Lighting Fabrication & Powder Coating, LLC. Conroe, TX

http://www.divinelighting.net customerservice@divinelighting.net PH: 936-494-3900 FX: 936-494-3910