

WALL SCONCE L SERIES



DIMENSIONS:

- 33 - 3"W x 3"H
- 34 - 3"W x 4"H
- 44 - 4"W x 4"H
- 45 - 4"W x 5"H

Lengths: 2' - 24" 3' - 35" 4' - 46"



Project:	
Location(s):	
Type:	
Qty:	
Date:	

PRODUCT SPECIFICATIONS

Description:

A Rectangular Wall Mount with
Up / Down Lens

Materials:

20ga. G90 Galvanized Steel

Finish:

Powder Coated

Lens:

Polycarbonate Options

LED:

Integrated LED Array

Listing:

Damp List to Meet UL1598 Standard

Driver Info:

120V

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment



ADA Compliant



ORDER INFORMATION

Call Factory For Fluorescent Options

MODEL	DIMENSIONS	FINISH	WATTAGE	KELVIN	LENS	LENGTH	OPTIONS
Model LUD - Up/down LDN - down LUP - Up	Dimensions 33 34 44 45	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	Wattage (24") LED21 - 21W LED 2100Lms LED36 - 36W LED 3600Lms Wattage(36") LED21 - 23W LED 2300Lms LED52 - 52W LED 5200Lms Wattage (48") LED40 - 40W LED 4000 Lms LED64 - 64W LED 6400 Lms	Kelvin 30 - 30K 35 - 35K 40 - 40K	Lens WP - White Polycarbonate FP - Frosted Polycarbonate	Length 2 - 24" Length 3 - 35" Length 4 - 46" Length <i>custom lengths available</i>	Options EM5 - 500Lm Emergency EM12 - 1200Lm Emergency DV - 120/277 Dual Volt DIM0-10V - 0-10V Dimmable MOT50 - Motion Sensor MOT100 - Motion Sensor

Divine Lighting & Mfg., LLC.
3704 Hilltop Dr. Ste. 200

<http://www.divinelighting.net>
customerservice@divinelighting.net

PH: 936-494-3900
FX: 936-494-3910

As led performance and lumen output becomes more efficient, specifications are subject to change without notice