

AREA AND SITE LIGHTING

MSL8 SERIES

Standard Product Specifications

- Materials:**
Die-Cast Aluminum Housing

Finish:
Powder Coated

Lens:
Optics

LED:
Integrated LED Array
- Listing:**
Wet List to Meet UL 1598 Standard

Driver Info:
120/277V

Installation Information:
Install by Qualified Electrician

Warranty:
2 Years From Date of Shipment

DIMENSIONS:

MSL8M - 13”W x 15.6”L

MSL8L - 13”W x 24.9”L



MODEL	FINISH	WATTAGE - CCT	KELVIN - CCT	TYPE	OPTIONS
<u>Model</u> MSL8M MSL8L	<u>Finish</u> DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color	<u>Wattage(MSL8M)</u> LED100 - 100W LED 10800 Lms LED140 - 140W LED 14000 Lms LED180 - 180W LED 18000 Lms <u>Wattage(MSL8L)</u> LED250 - 250W LED 25000 Lms LED300 - 300W LED 30000 Lms LED400 - 400W LED 40000 Lms	<u>Kelvin</u> 30 - 30K 40 - 40K 50 - 50K	<u>Type</u> II - Type II III - Type III IV - Type IV V - Type V	<u>Options</u> PC - Photocell