

WALL SCONCES

RUDL/SQUDL

Standard Product Specifications

Materials:

20ga. G90 Galvanized Steel Housing

Finish:

Powder Coated

Lens:

White Polycarbonate

LED:

Integrated LED Array

Listing:

Wet List to Meet UL 1598 Standard

Driver Info:

120V

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment

DIMENSIONS:

RUDL9X5 - 9"W x 5"H x 4"E

RUDL12X5 - 12"W x 5"H x 4"E

SQUDL - 5"Sq. x 4"E

(Custom Sizes Available - Call Customer Service)



| MODEL | FINISH | WATTAGE | KELVIN | OPTIONS |
|---|---|--|---|---|
| Model RUDLXXX SQUDLXXX Replace XXX with Width, Length, and Height in Inches | Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color | Wattage (RUDL) LED10 - 10W LED 1000 Lms LED12 - 12W LED 1200 Lms LED20 - 20W LED 2000 Lms* *RUDL12x5 Only Wattage (SQUDL) LED10 - 10W LED 1000 Lms LED12 - 12W LED 1200 Lms LED20 - 20W LED 2000 Lms | Kelvin 30 - 30K 35 - 35K 40 - 40K 50 - 50K | Options DV - Dual Volt 120/277V DIM - 0-10V Dimmable EM5 - 500 Lms Emergency* EM10 - 1000 Lms Emergency* *RUDL12x5 or Larger Only |