

WALL SCONCES S SERIES



S612 : 6"W x 12"H x 4"E
S616 : 6"W x 16"H x 4"E
S624 : 6"W x 24"H x 4"E

S812 : 8"W x 12"H x 4"E
S815 : 8"W x 15"H x 4"E
S824 : 8"W x 24"H x 4"E

S1012 : 10"W x 12"H x 4"E
S1015 : 10"W x 15"H x 4"E
S1024 : 10"W x 24"H x 4"E

Frame edge adds:
1.5" W and .5"H

Add "SQ" to the start for
square sconce
Ex: SQ612, SQ1024

Project:	
Location(s):	
Type:	
Qty:	
Date:	

PRODUCT SPECIFICATIONS

Description:

Partial Round Sconce with Different Patterns

Materials:

Galvanized Steel Pan and Housing

Finish:

Powder Coated

Lens:

White Acrylic

Lens Top/ Lens Bottom Standard

LED:

Integrated LED Array

Listing:

Wet List to Meet UL 1598 Standard

Driver Info:

120V

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment



ADA Compliant



Fixtures over 24" high may require an additional horizontal center bar(s) for support

MODEL	FRAME / PATTERN	FINISH	WATTAGE	KELVIN	LENS	OPTIONS	
Model S612 SQ612 S616 SQ615 S624 SQ624 S812 SQ812 S815 SQ815 S824 SQ824 S1012 SQ1012 S1015 SQ1015 S1024 SQ1024	Frame F - Add Outside Frame *Optional	Pattern # - Pattern #	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	Wattage (12") LED12 - 12W LED 1200 Lms LED22 - 22W LED 2200 Lms Wattage (15") LED12 - 12W LED 1200 Lms LED22 - 22W LED 2200 Lms Wattage (24") LED21 - 21W LED 2100 Lms LED36 - 36W LED 3600 Lms	Kelvin 30 - 30K 35 - 35K 40 - 40K 50 - 50K	Lens WA - White Acrylic	Options DV - 120/277 Dual Volt PC - Photocell EM5 - 500 Lm Emergency EM12 - 1200 Lm Emergency (min 15" height) DIM0-10V - 0-10V Dimmable MT - Metal Top MB - Metal Bottom

Divine Lighting & Mfg., LLC.
3704 Hilltop Dr. Ste. 200

<http://www.divinelighting.net>
customerservice@divinelighting.net

PH: 936-494-3900
FX: 936-494-3910

As led performance and lumen output becomes more efficient, specifications are subject to change without notice