

FLOODS

SB12 / SB16 / SB22



DIMENSIONS:

SB12 - 12.5”Sq x 5.375”H

SB16 - 16.35”Sq x 7”H

SB22 - 22”Sq x 10.25”H

Project:	
Location(s):	
Type:	
Qty:	
Date:	

PRODUCT SPECIFICATIONS

Description:

Flood Light With Mounting Arm
Options

Materials:

Die Cast Aluminum Housing with
Conduit Access on 5 Sides

Finish:

Powder Coated

Lens:

Frosted Glass

LED:

Integrated LED Array

Listing:

Wet List to Meet UL 1598 Standard

Driver Info:

120/277V

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment



Shown with Yoke



Shown with LSF & Hood



SB16

ORDER INFORMATION

Call Factory For Fluorescent Options

MODEL	FINISH	WATTAGE	KELVIN	TYPE	OPTIONS
Model SB12 SB16 SB22	Finish DB - Dark Bronze BL - Black WH - White AS - Anodized Silver CC - Custom Color	Wattage(SB12) LED30 - 30W LED 3000 Lms LED55 - 55W LED 5900 Lms Wattage(SB16) LED30 - 30W LED 3000 Lms LED45 - 45W LED 4900 Lms LED55 - 55W LED 5900 Lms LED80 - 80W LED 8500 Lms LED120 - 120W LED 11300 Lms Wattage(SB22) LED80 - 80W LED 8500 Lms LED120 - 120W LED 11300 Lms	Kelvin 30 - 30K 40 - 40K 50 - 50K	Type II - Type 2 Reflector III - Type 3 Reflector IV - Type 4 Reflector V - Type 5 Reflector	Options PC - Photocell H - Hood (Cutoff Shield) FLEM6 - 6” Arm FLEM10 - 10” ARM YK - Yoke LSF - Large Slip Fitter C - Cutoff Reflector