WALL SCONCES TURBTS



Standard Product Specifications

Materials:

Extruded Aluminum Housing Finish: Powder Coated Lens: Tempered Clear Flat Glass LED: Integrated LED Array

Listing:

Wet List to Meet UL 1598 Standard FWC Turtle-Safe 585-595 nm Driver Info:

120/277V 0-10V Dimmable Standard

Installation Information:

Install by Qualified Electrician Warranty: 2 Years From Date of Shipment

DIMENSIONS: 5.75"Dia. x 8.875"L x 16.25"H





MODEL	FINISH	WATTAGE	KELVIN	OPTICS	OPTIONS
<u>Model</u> TURBTS	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color	Wattage LED20 - 20W	<u>Kelvin</u> 14 - 14K	<u>Optics</u> N - Narrow Beam M - Medium Beam W - Wide Beam	Options PC - Photocell EM5 - 500 Lms Emergency EM12 - 1200 Lms Emergency
Divine Lighting	Fabrication & Powder Coat Conroe, TX	0	http://www.divinelighting.net customerservice@divinelighting.net		PH: 936-494-3900 FX: 936-494-3910

As led performance and lumen output becomes more efficient, specifications are subject to change without notice