

# WALL SCONCES UD SERIES



### DIMENSIONS:

<b>UD4</b> - 3.5"W x H x 4"E <b>ADA</b>	<b>UD812</b> - 8"W x 12"H x 10.5"E
<b>UD512</b> - 5"W x 12"H x 7.5"E	<b>UD815</b> - 8"W x 15"H x 10.5"E
<b>UD515</b> - 5"W x 15"H x 7.5"E	<b>UD818</b> - 8"W x 18"H x 10.5"E
<b>UD518</b> - 5"W x 18"H x 7.5"E	<b>UD1018</b> - 10"W x 18"H x 12.5"E
<b>UD612</b> - 6"W x 12"H x 8.5"E	<b>UD1024</b> - 10"W x 24"H x 12.5"E
<b>UD615</b> - 6"W x 15"H x 8.5"E	<b>UD1028</b> - 10"W x 28"H x 12.5"E
<b>UD618</b> - 6"W x 18"H x 8.5"E	

Project:	
Location(s):	
Type:	
Qty:	
Date:	

### PRODUCT SPECIFICATIONS

#### Description:

An Sleek Cylinder Up/Down Wall Sconce

**ADA Compliant Optional**

#### Materials:

Aluminum Housing

#### Finish:

Powder Coated

#### Lens:

UD5-UD6 : Clear Glass Prismatic

UD8-UD10 : Frosted Polycarbonate

#### LED:

Integrated LED Array

#### Listing:

Wet List to Meet UL 1598 Standard

#### Driver Info:

120V

#### Installation Information:

Install by Qualified Electrician

#### Warranty:

2 Years From Date of Shipment

Custom heights available



ADA  
Compliant  
Extension

### ORDER INFORMATION

Call Factory For Fluorescent Options

MODEL		FINISH	WATTAGE		KELVIN	OPTIONS
<b>Model</b>	<b>Model (con.)</b>	<b>Finish</b>	<b>Wattage (UD5-UD6)</b>	<b>Wattage (UD10)</b>	<b>Kelvin</b>	<b>Options</b>
UD4	UD812	DB - Dark Bronze	LED10 - 10W LED 1000 Lms*	LED30 - 30W LED 3000 Lms	30 - 30K	DV - 120/277 Dual Volt
UD512	UD815	BL - Black	LED20 - 20W LED 2000 Lms*	LED40 - 40W LED 4000 Lms	40 - 40K	W - Wet List
UD515	UD818	AS - Anodized Silver	LED30 - 30W LED 3000 Lms	LED90 - 90W LED 11,600 Lms	50 - 50K	PC - Photocell
UD518	UD1018	WH - White	**UD4 wattages			LT - Lens Top
UD612	UD1024	CC - Custom Color	<b>Wattage (UD8)</b>			LB - Lens Bottom
UD615	UD1028		LED20 - 20W LED 2000 Lms			(LT & LB is Wet Listed)
UD618			LED30 - 30W LED 3000 Lms			ADA - ADA Compliant
			LED40 - 40W LED 4000 Lms			

Divine Lighting & Mfg., LLC.  
3704 Hilltop Dr. Ste. 200

<http://www.divinelighting.net>  
[customerservice@divinelighting.net](mailto:customerservice@divinelighting.net)

PH: 936-494-3900  
FX: 936-494-3910

As led performance and lumen output becomes more efficient, specifications are subject to change without notice