



DIMENSIONS:

WPG1140

8.62”W x 7.6”H x 5.1”E

WPG1160

14.3”W x 9.3”H x 5.7”E

Project:	
Location(s):	
Type:	
Qty:	
Date:	

PRODUCT SPECIFICATIONS

Description:

Smooth LED Wallpack with 2 Size Options for Optimal Light Output

Materials:

Die Cast Aluminum Housing

Finish:

Powder Coated

Lens:

High-Impact Resistant Tempered Glass

LED:

Integrated LED Array

Listing:

Wet List to Meet UL 1598 Standard

Driver Info:

120/277V

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment



1140



1160



ORDER INFORMATION
Call Factory For Fluorescent Options

MODEL	FINISH	WATTAGE	KELVIN	OPTIONS
Model WPG1140 WPG1160	Finish DB - Dark Bronze (Standard) BL - Black AS - Anodized Silver WH - White CC - Custom Color	Wattage(1140) LED13 - 13W LED 1607 Lms LED20 - 20W LED 2766 Lms LED28 - 28W LED 3482 Lms Wattage(1160) LED40 - 40W LED 4303 Lms LED55 - 55W LED 5600 Lms LED79 - 79W LED 9896 Lms	Kelvin 30 - 30K 40 - 40K 50 - 50K	Options PC - Photocell MOT - Motion