



DIMENSIONS:

WPG1850

7.48"W x 8"H x 2.81"E

WPG2850

14.17"W x 12.8"H 4.9"E

Project:	
Location(s):	
Type:	
Qty:	
Date:	

PRODUCT SPECIFICATIONS

Description:

Slim Wallpack with Multiple Mounting Options

Materials:

Die Cast Aluminum Housing

Finish:

Powder Coated

Lens:

High-Impact Resistant Tempered Glass

LED:

Integrated LED Array

Listing:

Wet List to Meet UL 1598 Standard

Driver Info:

120/277V

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment



Knuckle
+4.25"E



WPG1850
Slip Fitter
+8.07"E



Yoke
+6.14"E



WPG2850
Slip Fitter
+8.26"E



WPG2850
Yoke
+7.72"E



Quick Mount
Standard

ORDER INFORMATION

Call Factory For Fluorescent Options

MODEL	FINISH	WATTAGE	KELVIN	OPTIONS
Model WPG1850 WPG2850	Finish DB - Dark Bronze (Standard) BL - Black AS - Anodized Silver WH - White CC - Custom Color	Wattage(1850) LED14 - 14W LED 1400 Lms LED22 - 22W LED 2200 Lms LED30 - 30W LED 3000 Lms LED40 - 40W LED 4000 Lms LED58 - 58W LED 5800 Lms Wattage(2850) LED88 - 88W LED 8800 Lms LED150 - 150W LED 15000 Lms	Kelvin 30 - 30K 40 - 40K 50 - 50K	Options EM5 - 500 Lm Emergency EM12 - 1200 Lm Emergency PC - Photocell KNL - Knuckle SF - Slip Fitter YK - Yoke