



DIMENSIONS:

WPWL

9.75"W x 11.25"H x 6.125"E

WPWS

6.625"W x 7.875"H x 4.5"E

Project:	
Location(s):	
Type:	
Qty:	
Date:	

PRODUCT SPECIFICATIONS

Description:

Narrow Wallpack Cutoff in LED with Multiple Mounting Options

Materials:

Cast Aluminum Gasketed Housing

Finish:

Powder Coated

Lens:

Impact Resistant Tempered Clear Flat Glass

LED:

Integrated LED Array

Listing:

CSA Listed for Wet Locations IP65

Dark Sky Compliant

Driver Info:

120/277V

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment



Shown with optional knuckle



View when mounted on wall



Shown with optional slip fitter

ORDER INFORMATION

Call Factory For Fluorescent Options

MODEL	FINISH	WATTAGE	KELVIN	OPTIONS
Model WPWL WPWS	Finish DB - Dark Bronze (Standard) BL - Black AS - Anodized Silver WH - White CC - Custom Color	Wattage (WPWS) LED20 - 20W LED 2000 Lms LED40 - 40W LED 4000 Lms Wattage (WPWL) LED60 - 60W LED 6000 Lms LED80 - 80W LED 8000 Lms	Kelvin 40 - 40K 50 - 50K	Options KNL - Knuckle SF - Slip Fitter PC - Photocell

