



**DIMENSIONS:**

- YP164 Small - 7.3"W x 4.5"H x 9.3"E
- YP164 Medium - 10.3"W x 4.5"H x 11.75"E
- YP164 Large - 10.68"W x 4.75"H x 14"E
- YP164 XLarge - 10.75"W x 4.75"H x 18.5"E

|              |  |
|--------------|--|
| Project:     |  |
| Location(s): |  |
| Type:        |  |
| Qty:         |  |
| Date:        |  |

PRODUCT SPECIFICATIONS

**Description:**  
Multi-function LED Wallpack with Four Convenient Sizes

**Materials:**  
Die Cast Aluminum Housing

**Finish:**  
Powder Coated

**Lens:**  
Clear Polycarbonate

**LED:**  
Integrated LED Array

**Listing:**  
Wet List to Meet UL 1598 Standard

**Driver Info:**  
120/277V

**Installation Information:**  
Install by Qualified Electrician

**Warranty:**  
2 Years From Date of Shipment



YP164S



YP164M



YP164L



YP164XL

ORDER INFORMATION  
Call Factory For Fluorescent Options

| MODEL   | FINISH   | WATTAGE  | KELVIN  | MOUNT   | OPTIONS   |
|---|--|--|---|---|---|
| <b>Model</b><br>YP164S<br>YP164M<br>YP164L<br>YP164XL | <b>Finish</b><br>DB - Dark Bronze (Standard)<br>BL - Black<br>AS - Anodized Silver<br>WH- White<br>CC - Custom Color | <b>Wattage (YP164S)</b><br>LED18 - 18W LED 1800 Lms<br>LED25 - 25W LED 2500 Lms<br><b>Wattage (YP164M)</b><br>LED50 - 50W LED 5000 Lms<br>LED70 - 70W LED 7000 Lms<br><b>Wattage (YP164L)</b><br>LED100 - 100W LED 1200 Lms<br>LED120 - 120W LED 14400 Lms<br><b>Wattage (YP164XL)</b><br>LED150 - 150W LED 18000<br>LED180 - 180W LED 21600 | <b>Kelvin</b><br>30 - 30K<br>40 - 40K<br>50 - 50K | <b>Mount</b><br>WM - Wall Mount<br>LSF - Slip Fitter<br>SAS - Straight Arm for Square Pole<br>SAR - Straight Arm for Round Pole | <b>Options</b><br>PC - Photocell<br>MOT - Motion<br>EM5 - 500 Lm Emergency<br>EM12 - 1200 Lm Emergency<br>I - Type 1 (small only)<br>II - Type 2 (M, L, XL)<br>III - Type3 (M, L, XL) |