



DIMENSIONS:
15.5"W x 4.8"H x 23.4"E

Project:	
Location(s):	
Type:	
Qty:	
Date:	

PRODUCT SPECIFICATIONS

Description:
Highpowered Finned LED Wallpack

Materials:
Die Cast Aluminum

Finish:
Powder Coated

Lens:
Clear Polycarbonate

LED:
Integrated LED Array

Listing:
Wet List to Meet UL 1598 Standard

Driver Info:
120/277V

Installation Information:
Install by Qualified Electrician

Warranty:
2 Years From Date of Shipment



ORDER INFORMATION
Call Factory For Fluorescent Options

MODEL	FINISH	WATTAGE	KELVIN	MOUNT	OPTIONS
<u>Model</u> YP722	<u>Finish</u> DB - Dark Bronze (Standard) BL - Black AS - Anodized Silver WH- White CC - Custom Color	<u>Wattage</u> LED150 - 150W LED 18000 Lms LED180 - 180W LED 21600 Lms LED240 - 240W LED 28800 Lms LED280 - 280W LED 33600 Lms	<u>Kelvin</u> 30 - 30K 40 - 40K 50 - 50K	<u>Mount</u> WM - Wall Mount LSF - Slip Fitter SAS - Straight Arm for Square Pole SAR - Straight Arm for Round Pole	<u>Options</u> PC - Photocell MOT - Motion EM5 - 500 Lm Emergency EM12 - 1200 Lm Emergency II - Type 2 III - Type 3 IV - Type 4