



DIMENSIONS:

- YP737 Small - 14.2"W x 2.75"H x 15.8"E
- YP737 Medium - 14.2"W x 2.75"H x 19"E
- YP737 Large - 14.2"W x 2.75"H x 22"E
- YP737 XLarge - 14.2"W x 2.75"H x 25.2"E

| | |
|--------------|--|
| Project: | |
| Location(s): | |
| Type: | |
| Qty: | |
| Date: | |

PRODUCT SPECIFICATIONS

Description:
Slim LED Wallpack with Four Convenient Sizes

Materials:
Die Cast and Extruded Aluminum

Finish:
Powder Coated

Lens:
Clear Polycarbonate

LED:
Integrated LED Array

Listing:
Wet List to Meet UL 1598 Standard

Driver Info:
120/277V

Installation Information:
Install by Qualified Electrician

Warranty:
2 Years From Date of Shipment



ORDER INFORMATION
Call Factory For Fluorescent Options

| MODEL | FINISH | WATTAGE | KELVIN | MOUNT | OPTIONS |
|---|--|---|---|---|--|
| Model YP737S YP737M YP737L YP737XL | Finish DB - Dark Bronze (Standard) BL - Black AS - Anodized Silver WH- White CC - Custom Color | Wattage (YP737S) LED120 - 120W LED 14400 Lms Wattage (YP737M) LED180 - 180W LED 21600 Lms Wattage (YP737L) LED240 - 240W LED 28800 Lms Wattage (YP737XL) LED300 - 300W LED 36000 Lms | Kelvin 30 - 30K 40 - 40K 50 - 50K | Mount WM - Wall Mount LSF - Slip Fitter SAS - Straight Arm for Square Pole SAR - Straight Arm for Round Pole | Options PC - Photocell MOT - Motion EM5 - 500 Lm Emergency EM12 - 1200 Lm Emergency II - Type 2 III - Type 3 IV - Type 4 |