

Standard Product Specifications

Materials:

Steel

Finish:

Powder Coated


Hand Hole Cover:

Pole Height	Pole Bury Depth
8'	2'
10'	
12'	
15'	3'
18'	
20'	4'
24'	
30'	5'

The Chart Above is a Guideline - Consult With an Engineer for Site Specific Requirements.



Hand Hole 18" Above Ground
Access Hole 18" Below Ground



Divine Standard Drill Pattern

MODEL	SHAFT	SCHEDULE	LENGTH	BURY DEPTH	OPTIONS	FINISH
Model POLE-DB-RSP (Round Steel Direct Bury)	Shaft 4 - 4"OD	Schedule/Gauge 11 - Schedule 11	Length(Overall) 10' 12' 15' 16'	Bury Depth BX - Custom Bury Depth (In Feet)	Options 190 - (1) 90 Degree Hole 2180 - (2) 180 Degree Holes GFCI - GFCI Receptacle GFCILOCK - GFCI Lock TENON 2 3/8 x 3 TENON 3.5 x 3 EYE - Eye Hooks	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color

**Customer is responsible for providing fully dimensioned drill patterns when using heads from other manufacturers; otherwise, the standard Divine Lighting drill pattern will be used.

**Customer must specify the orientation of fixtures on the pole when ordering. This information can be found in the options section, e.g. 190, 2180, etc.

**Divine Lighting is not responsible for inconsistencies between poles, fixtures, and parts produced by different manufacturers, and cannot guarantee proper fitting between such components.