

Decorative Area & Site Luminaire
Architectural Outdoor Lighting Solution



SPECIFICATIONS

EPA: 1.46 ft²
Height (H1): 12.34"
Diameter (D1): 22"
Weight: 26 lbs.

PERFORMANCE

Delivered Lumens:
3,000 – 9,500 lumens (depending on configuration)
Wattage:
30W – 95W LED System
Color Characteristics:
CCT: 3000K / 3500K / 4000K / 5000K
CRI: ≥80 standard

ELECTRICAL

Input Voltage:
120–277V
Dimming:
0–10V (DIM Option)
LEDs:
High-efficacy LEDs mounted to metal-core circuit boards for optimized thermal management.

CONSTRUCTION

Housing:
Spun Aluminum Housing with nominal wall thickness of 0.100" and fully welded stem assembly for structural rigidity and long-term durability.
*All aluminum components are manufactured from corrosion-resistant alloys suitable for outdoor architectural environments.
Finish:
Corrosion-resistant Super Durable Powder Coat Finish
Lens:
Clear Flat Glass
LED Source:
Integrated LED Array

INSTALLATION

Installation by qualified electrician.
See mounting arm options for configuration details.

LISTINGS

ETL Listed for Wet Locations.
Conforms to UL 1598 and CSA standards.

WARRANTY

Standard 2-Year Limited Warranty
Optional 5-Year and 7-Year Extended Warranties Available
Note: Specifications subject to change without notice. Actual performance may vary depending on installation environment and operating conditions.



ORDERING GUIDE

MODEL	FINISH	PERFORMANCE	KELVIN	OPTIONS
Model DPT-F44-A DPT-F44-B DPT-F44-C DPT-F44-D	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	Performance LED30 - 30W LED 3000 Lms LED60 - 60W LED 6000 Lms LED95 - 95W LED 9500 Lms	Kelvin 30 - 30K 35 - 35K 40 - 40K 50 - 50K	Options 5Y - 5 Year Warranty 7Y - 7 Year Warranty DIM - 0-10V Dimmable