

Standard Product Specifications

Materials:
 Cast Aluminum Housing
Finish:
 Powder Coated
Lens:
 Clear Glass
LED:
 Integrated LED Array

Listing:
 Wet List to Meet UL 1598 Standard
Driver Info:
 120/277V
Installation Information:
 Install by Qualified Electrician
Warranty:
 2 Years From Date of Shipment
 5 & 7 Year Warranties Available

DIMENSIONS:
DPT031A - 19.5”Dia. x 27.5”H
DPT031B - 31”W x 11.8”H



Mounts on 3.5” Tenon



DPT031A



DPT031B

| MODEL | FINISH | WATTAGE | KELVIN | TYPE | OPTIONS |
|------------------------------------|---|---|---|---|--|
| Model DPT031A DPT031B | Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color | Wattage LED30 - 30W LED 3000 Lms LED60 - 60W LED 6000 Lms LED100 - 100W LED 10000 Lms | Kelvin 30 - 30K 40 - 40K 50 - 50K | Type III - Type III IV - Type IV V - Type V | Options 5Y - 5 Year Warranty 7Y - 7 Year Warranty DIM - 0-10V Dimmable PC - Photocell HSS90 - 90 Degree House Side Shield HSS180 - 180 Degree House Side Shield |