POST TOPS DPT085



Standard Product Specifications

Materials:

Die-Casted Aluminum Housing Finish: Powder Coated Lens: Clear Polycarbonate LED: Integrated LED Array

Listing: Wet List to Meet UL 1598 Standard **Driver Info:** 120/277V **Installation Information:** Install by Qualified Electrician Warranty: 2 Years From Date of Shipment

DIMENSIONS: 27.17"W x 18.90"H



REV 51724 1400 ACE



MODEL	FINISH	WATTAGE	KELVIN	ТҮРЕ	OPTIONS
Model DPT085	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color	Wattage LED30 - 30W LED 3450 Lms LED50 - 50W LED 5750 Lms LED60 - 60W LED 6900 Lms LED70 - 70W LED 8050 Lms	Kelvin 30 - 30K 35 - 35K 40 - 40K 50 - 50K	<u>Type</u> <u>II</u> - Type II <u>III</u> - Type III <u>V</u> - Type V	<u>Options</u> DIM - 0-10V Dimmable
Divine Lighting Fabrication & Powder Coating, LLC. http://www.divinelighting.net Conroe, TX customerservice@divinelighting.net					PH: 936-494-3900 FX: 936-494-3910

As led performance and lumen output becomes more efficient, specifications are subject to change without notice