

Standard Product Specifications

Materials:

Die-Cast Aluminum

Finish:

Powder Coated

Lens:

Clear Polycarbonate

LED:

Integrated LED Array

Listing:

Wet List to Meet UL 1598 Standard

Driver Info:

120/277V

Installation Information:

Install by Qualified Electrician

Warranty:

2 Years From Date of Shipment
5 & 7 Year Warranties Available

DIMENSIONS:

15.75”Dia. x 7.75”H



MODEL	FINISH	WATTAGE	KELVIN	LENS	TYPE	OPTIONS
Model EPTS101-CBLH	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	Wattage LED25 - 25W LED 2900Lms LED36 - 36W LED 4000Lms LED60 - 60W LED 7200Lms LED79 - 79W LED 9100Lms LED98 - 98W LED 10500 Lms	Kelvin 30 - 30K 35 - 35K 40 - 40K 50 - 50K	Lens CP - Clear Polycarbonate FP - Frosted Polycarbonate* *Only available without optics	Type (CP Only) II - Type II III - Type III IV - Type IV V - Type V	Options 5Y - 5 Year Warranty 7Y - 7 Year Warranty DIM - 0-10V Dimmable PC - Photocell MOT - Motion Sensor