

Standard Product Specifications

**Materials:**

20ga. G90 Galvanized Steel

**Finish:**

Powder Coated

**Lens:**

White Polycarbonate

**LED:**

Integrated LED Array

**Listing:**

Wet List to Meet UL 1598 Standard

**Driver Info:**

120/277V

**Installation Information:**

Install by Qualified Electrician

**Warranty:**

2 Years From Date of Shipment  
5 & 7 Year Warranties Available

**DIMENSIONS:**

LFSQ24 - 24"L x 5"H x 3"D

LFSQ36 - 36"L x 5"H x 3"D

LFSQ48 - 48"L x 5"H x 3"D

LFSQ72 - 72"L x 5"H x 3"D

LFSQ96 - 96"L x 5"H x 3"D



MODEL	FINISH	WATTAGE	KELVIN	OPTIONS
<b>Model</b> LFSQ24 LFSQ36 LFSQ48 LFSQ72 LFSQ96	<b>Finish</b> DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	<b>Wattage(LFSQ24)</b> LED21 - 21W LED 2100 Lms LED36 - 36W LED 3600 Lms  <b>Wattage(LFSQ36)</b> LED23 - 23W LED 2300 Lms LED46 - 46W LED 4600 Lms  <b>Wattage(LFSQ48)</b> LED36 - 36W LED 3600 Lms LED64 - 64W LED 6400 Lms  <b>Wattage(LFSQ72)</b> LED46 - 46W LED 4600 Lms LED84 - 84W LED 8400 Lms  <b>Wattage(LFSQ96)</b> LED72 - 72W LED 7200 Lms LED128 - 128W LED 12800 Lms	<b>Kelvin</b> 30 - 30K 35 - 35K 40 - 40K 50 - 50K	<b>Options</b> 5Y - 5 Year Warranty 7Y - 7 Year Warranty DIM - 0-10V Dimmable PC - Photocell EM5 - 500 Lms Emergency EM12 - 1200 Lms Emergency