

POST TOPS
QPT12Q

Standard Product Specifications

Materials:
Die-Cast Aluminum Housing
Finish:
Powder Coated
Lens:
Clear Polycarbonate
LED:
Integrated LED Array

Listing:
Wet List to Meet UL 1598 Standard
Driver Info:
120/277V
0-10V Dimmable Standard
Installation Information:
Install by Qualified Electrician
Warranty:
2 Years From Date of Shipment
5 & 7 Year Warranties Available

DIMENSIONS:
11.5"W x 17.5"H
10.5" Head Diameter



Lumen Table

*Available Lumens Based on Kelvin Selected

	10W	19W	28W
Type II	833-893	1,666-1,787	2,499-2,680
Type III	876-939	1,752-1,879	2,628-2,818
Type IV	867-930	1,735-1,860	2,602-2,790
Type V	918-984	1,836-1,968	2,753-2,952

MODEL	FINISH	WATTAGE	KELVIN	TYPE	OPTIONS
Model QPT12Q	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	Wattage LED10 - 10W LED LED19 - 19W LED LED28 - 28W LED	Kelvin 30 - 30K 40 - 40K 50 - 50K	Type II - Type II III - Type III IV - Type IV V - Type V	Options 5Y - 5 Year Warranty 7Y - 7 Year Warranty PC - Photocell EM5 - 500 Lms Emergency EM12 - 1200 Lms Emergency