

Standard Product Specifications

Materials:
Cast Aluminum Houston
Finish:
Powder Coated
Lens:
Clear Polycarbonate
LED:
Integrated LED Array

Listing:
List to Meet UL 1598 Standard
Driver Info:
120/277V
Installation Information:
Install by Qualified Electrician
Warranty:
2 Years From Date of Shipment
5 and 7 Year Warranties Available

DIMENSIONS:
QSL32 - 18" Dia. x 8.5"H x 23.25"E



MODEL	FINISH	WATTAGE	KELVIN	TYPE	OPTIONS
Model QSL32	Finish DB - Dark Bronze BL - Black AS - Anodized Silver WH - White CC - Custom Color	Wattage LED37 - 37W LED 5400 Lms LED65 - 65W LED 9600 Lms LED100 - 100W LED 14800 Lms LED140 - 140W LED 20000 Lms <i>*Lower lumen output on type IV</i>	Kelvin 30 - 30K* 40 - 40K 50 - 50K <i>*37W & 65W Only</i>	Type II - Type 2 III - Type 3 IV - Type 4 V - Type 5	Options 5Y - 5 Year Warranty 7Y - 7 Year Warranty DIM0-10 - 0-10V Dimmable MOT - Motion Sensor PC - Photocell EM5 - 500 Lms Emergency EM12 - 1200 Lms Emergency