wall sconces **RUDL**



Standard Product Specifications

Materials: Extruded Aluminum Tubing Finish:

Powder Coated Lens: White Polycarbonate LED: Integrated LED Array

Listing: Wet List to Meet UL 1598 Standard Driver Info: 120V Installation Information: Install by Qualified Electrician Warranty: 2 Years From Date of Shipment

DIMENSIONS: RUDL9X5 - 9"W x 5"H x 4"E **RUDL12X5** - 12"W x 5"H x 4"E

(Custom Sizes Available - Call Customer Service)





MODEL	FINISH	WATTAGE	KELVIN	OPTIONS
Model RUDLXXX Replace XXX with Width, Length, and Height in Inches	<u>Finish</u> DB - Dark Bronze BL - Black AS - Anodized Silver WH- White CC - Custom Color	Wattage LED10 - 10W LED 1000 Lms LED12 - 12W LED 1200 Lms LED20 - 20W LED 2000 Lms* *RUDL12x5 Only	<u>Kelvin</u> 30 - 30K 35 - 35K 40 - 40K 50 - 50K	Options DV - Dual Volt 120/277V DIM - 0-10V Dimmable EM5 - 500 Lms Emergency* EM10 - 1000 Lms Emergency* *RUDL12x5 or Larger Only
Divine Lighting Fabrication & Powder Coating, LLC. Conroe, TX		http://www.divinelighting.net customerservice@divinelighting.net	PH: 936-494-3900 FX: 936-494-3910	

As led performance and lumen output becomes more efficient, specifications are subject to change without notice